



- IP network video recorder
- 16-channel record
- 8Mp (4K) support
- 1xSATA (max. 14Tb)
- ONVIF 2.4 protocol support
- Smart functions support
- Support mobile monitoring:
iOS & Android
- Ability to work with Partizan
Cloud Storage
- Remote access to the device
with Partizan MAC

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global/>



System		
Model		NVH-1622
Version		1.1 Cloud
SKU		6627
Maximum connected cameras, pcs.		16
Operating system		Embedded Linux
Simultaneous multi-channel real-time recording		+
Playback		+
Network operation		+
USB backup		+
Record		
Record, channels x resolution @		16x8Mp@25, 8x8Mp@25, 4x8Mp@25, 1x8Mp@25
Record storage, HDD*/network		+/+
Video compression		H.264/H.265
Space occupation for 25 fps/1	Video H.264	~202Gb(8Mp), ~150Gb(5Mp), ~120Gb(4Mp), ~80Gb(2Mp),
	Video H.265	~135Gb(8Mp), ~100Gb(5Mp), ~80Gb(4Mp), ~53Gb(2Mp),
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps		1x8Mp@25, 2x5Mp@25, 4x2Mp@25
Backup mode, network/USB		+/+
Preview screen		1/2/4/6/8/9/16
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Audio		
Audio compression		G.711A
Two-way audio		+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Partizan MAC
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Default username		admin
Default password		admin
HTTP port		80
RTSP port		554
RTSP string		rtsp://IP_adress:554/user=admin&password=admin&channel=1&stream=0.sdp?
Control port		34567
Configuration software		Partizan
Monitoring program		Partizan, Partizan CMS, Partizan VMS
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+
Interface		
Display quality		4K; 2560x1440; 1920x1080; 1440x900; 1280x1024; 1280x720
Video	Inputs	-
	Outputs	1xVGA, 1xHDMI
Audio	Inputs	1xTRS(3.5mm)
	Outputs	1xTRS(3.5mm)
Alarm	Inputs	-
	Outputs	-
PTZ control, port/protocol support		Network
USB		2xUSB2.0
Internal SATA, pcs x max.Tb		1x14
External SATA, pcs x max.Tb		-
External eSATA, pcs x max.Tb		-
HDD operation mode		Single HDD

Smart Functions		
Channels / Functions		Human detection / Human Perimeter Intrusion Detection / Human Line Crossing Detection / Face Detection. Available only with Cloud-series cameras
Dimensions		
Size, mm		255x215x43
Weight, g		350
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	-
Power supply		DC12V, 5A
PoE/Class		-
Housing material, plastic/metal		-/+
Front material, plastic/metal		+/-
Operating temperature, °C		0 - +50
Warranty, years		3